

VA30S Series Glass Rotameter

VA30S glass rotameter are the new products of our company, compared with the other domestic products of the same type, it has advantages of high measuring precision, good interchangeability, multiple connection ways, especially the value of flow rate of the flow meter is in millimeter scale mark, which is capable of providing actual flow scale according to the temperature, pressure, density, and viscosity of different flows, solving the problem of indication correction.

Specification

DN (mm)	Model	Measure Range		Tube Length(mm)	Working Pressure(Bar)	Temp.
		Water (L/h)	Air (m ³ /h)			
15	VA30S-15 FA30S-15	4-40	0.12-1.2	300	≤1.0	-20°C ~200°C
		6-60	0.3-3			
		10-100	0.5-5			
		16-160	0.8-8			
		25-250	1.2-12			
		40-400	2-20			
25	VA30S-25 FA30S-25	63-630	2-20	300	≤1.0	-20°C ~200°C
		100-1000	3-30			
		160-1600	5-50			
		250-2500	8-80			
40	VA30S-40 FA30S-40	160-1600	5-50	300	≤0.9	-20°C ~200°C
		250-2500	8-80			
		400-4000	12-120			
50	VA30S-50 FA30S-50	400-4000	12-120	300	≤0.7	-20°C ~200°C
		630-6300	20-200			
		1000-10000	30-300			
		4000-16000				




VA

FA

Installation and Drawing size

(mm)	A×B	VA30S Screw Install			FA30S Flange Install			n-G
		L1	C	D	L2	E	F	
15	26×236	344	∅ 38	G1/2"	348	∅ 65	∅ 95	4-∅ 14
25	34×226	348	∅ 55	G 1 1/2"	348	∅ 85	∅ 115	4-∅ 14
40	44×226	370	∅ 70	G1"	370	∅ 110	∅ 145	4-∅ 18
50	60×216	380	∅ 90	G2"	370	∅ 125	∅ 160	4-∅ 18



FAW

sanitary fittings are available